

ESPECIFICAÇÕES CARPETE Coleção Arenito

CARPET TILE SPECIFICATIONS

CONSTRUCTION	Machine Tufted Hi-Low Loop Texture
PILE FIBER	100% Solution Dyed Nylon
TUFTING GAUGE	1/12 inch
PILE HEIGHT	4 mm.
PILE WEIGHT	22 oz./sq.yd. (745 gram/sq.m.)
BACKING STRUCTURE	EcoSoft , Recycled Cushion Backing
PILE TREATMENT	Stain Protector and Soil Repellent
TILE SIZE	50 x 50 cm.
BACKING OPTIONS AND WIDTH	Available, contact our sales representative for information

PERFORMANCE

WEAR CLASSIFICATION	Heavy Contract
CASTOR CHAIR RATING	Passes BS EN 985 > 2,4 Continuous use
DIMENSIONAL STABILITY	Passes BS EN 986 < 0,2 %
ELECTROSTATIC PROPERTIES	Passes AATOC 134 < 3 KV


FLAMMABILITY

HOT METAL NUT	Passes BS 4790 Low radius of effects of ignition
RADIANT PANEL TESTS	Passes ASTM E648, Class I
SMOKE DENSITY	Passes ASTM E662, Specific Optical Density < 450
RADIANT HEAT SOURCE	Passes AS ISO 9239,1,2003, CHF 10,7 kw/m ² / Smoke Value 60% minimum

ACOUSTIC BEHAVIOUR

SOUND ABSORPTION	EN ISO 354 and EN ISO 11654, Average Coefficient (α_w) 0,40 (H)
------------------	--

INSTALLATION METHOD



CERTIFICATION



Specifications are subject to normal manufacturing tolerances, and subject to change without prior notice.

As in all quality carpets, colors are subject to dye lot variations.